

# ADDITIVE MANUFACTURING POWDER

### L718 API AMPO / NI-BASED ALLOYS

Application Segments
----------------------

Additive Manufacturing Application

### **Available Product Variants**

15 - 45 μm

45 - 90 μm

### **Product Description**

The BÖHLER L718 AMPO is a hardenable nickel-base super alloy. This high heat-resistant material shows good strength properties at elevated temperatures up to  $750\,^{\circ}$  C, as well as excellent creep resistance up to  $700\,^{\circ}$  C. In addition, it shows excellent corrosion resistance and good printability. Essentially, the same properties can be achieved with printed components made from this powder as with bar material.

### **Process Melting**

VIGA

### Applications

- > 3D Printing direct metal deposition
- > Motorsport industry
- > CPI (incl. LNG, Urea)
- Other Components
- > Powder for additive manufacturing
- > 3D Printing selective laser melting
- > Civil and mechanical engineering
- > Oil & Gas / CPI
- Other Oil and Gas + CPI components
- > Automotive
- > Components for Industrial Gas Compressors
- Other Automotive Components (Turbochargers, Piston Rings, Sensors, etc.)
- > Other Power Generation Components

### Technical data

Material designation	
Alloy 718API	Market grade
NiCr19NbMo/ NiCr19Fe19Nb5Mo3	EN
N07718	UNS





## ADDITIVE MANUFACTURING POWDER

**BÖHLER L718API** AMPO

L718 API AMPO / NI-BASED ALLOYS

### Chemical composition (wt. %)

С	Cr	Мо	Ni	Ti	Al	Nb	В	Fe
0.02	18	3	Rest	0.95	0.5	5	0.003	18.5

### **Powder Properties**

#### Particle Size Distribution 15-45µm\*

Typical Values	D10	D50	D90
[µm]	18-24	29-35	42-50

<sup>\*</sup> Measurement of particle size distribution is based on ISO 13322-2 (Dynamic image analysis methods);

Apparent density\*\* min. 3.5 g/cm<sup>3</sup>

### **Mechanical Properties**

### With according Heat Treatment

With according rical recallions		
Tensile strength (Rm) (MPa)	1,290 to 1,390	
Yield strength (RP <sub>0,12</sub> ) (MPa)	1,050 to 1,110	
Elongation (%)	26 to 32	
Hardness (HRc)	43 to 49	
Impact Toughness (ISO-V)* (J)	58 to 68	

<sup>\*</sup> a -60 °C

Mechanical strength according to heat treatment API6acra - 150ksi

If other available product variants are listed in addition to long products, please note that these may differ in terms of melting process, technical data, delivery and surface condition as well as available product dimensions. For mandatory technical specifications, other requirements and dimensions, please contact our regional voestalpine BÖHLER sales companies. The data contained in this brochure is merely for general information and therefore shall not be binding on the company. We may be bound only through a contract explicitly stipulating such data as binding. Measurement data are laboratory values and can deviate from practical analyses. The manufacture of our products does not involve the use of substances detrimental to health or to the ozone layer.

### voestalpine BÖHLER Edelstahl GmbH & Co KG

Mariazeller Straße 25 8605 Kapfenberg, AT T. +43/50304/20-0

E. info@bohler-edelstahl.at

https://www.voestalpine.com/bohler-edelstahl/de/



<sup>\*\*</sup> Flowability and apparent density are based on DIN EN ISO 4490 resp. DIN EN ISO 3923-1.